



# evqpb

June 3, 2022

## Abstract

Event list quiescent particle background creator

## 1 Instruments/Modes

Instrument	Mode	SubMode
EPIC MOS	IMAGING	FULL FRAME WINDOW
EPIC PN	IMAGING	FULL FRAME WINDOW

## 2 Use

pipeline processing	yes
interactive analysis	yes

## 3 Description

The task **evqpb** creates for any given EPIC Full Frame science exposure an event list containing the associated quiescence particle background (QPB) extracted from the Filter Wheel Close data (FWC) repository. The event list containing the expected QPB, or instrumental background, can be used to correct spectra or images by subtracting this background component.

The task takes as input a science EPIC event list. This file will be used as a skeleton (keywords, EXPOSUXX and GTIs extensions) to create the associated QPB file. It also uses the Attitude History file and the SAS ODF environmental variable from the science exposure to properly project into sky-coordinates the events that will make the associated QPB file.

As the associated QPB event list contains less photons than the observation science data, we apply an oversampling factor F, which takes F times more exposure time of FWC data than the original science observation. The user can define this oversampling factor using the parameter **exposurefactor**.

To generate the associated QPB event list, events from the CCF are selected based on proximity in time to the science exposure and around the central time of the exposure. An oversampling factor F, will





## 5 Parameters

This section documents the parameters recognized by this task (if any).

Parameter	Mand	Type	Default	Constraints
-----------	------	------	---------	-------------

<b>table</b>	yes	filename		table specifier
--------------	-----	----------	--	-----------------

EPIC Full Frame event list

<b>useodfatt</b>	no	boolean	no	
------------------	----	---------	----	--

Whether to use the ODF and attitude file to calculate the attitude (yes) or the keywords in the input event table (no)

<b>attfile</b>	no	filename		Attitude History file
----------------	----	----------	--	-----------------------

Attitude History file of the current exposure

<b>exposurefactor</b>	no	integer	2	
-----------------------	----	---------	---	--

Oversampling exposure factor used to accumulate FWC data

<b>insitu</b>	no	boolean	no	
---------------	----	---------	----	--

Whether to produce a new event file (no) or overwrite an existing event file given in the **outset** parameter (yes)

<b>outset</b>	no	filename	evqpb.fit	
---------------	----	----------	-----------	--

Output file name

<b>overwritesubmode</b>	no	boolean	no	
-------------------------	----	---------	----	--

Overwrite imaging mode submode check

## 6 Errors

This section documents warnings and errors generated by this task (if any). Note that warnings and errors can also be generated in the SAS infrastructure libraries, in which case they would not be documented here. Refer to the index of all errors and warnings available in the HTML version of the SAS documentation.

### **WrongInstSubmode** (*error*)

evqpb can only be used in full frame mode

### **SubmodeCheckingDisabled** (*warning*)



This should be only used for testing purposes.

*corrective action:* This warning only appears if parameter `overwritesubmode` is enabled.

## 7 Input Files

1. an event file from an observation
2. an attitude file from the same observation

## 8 Output Files

1. an event file containing FWC events.

## 9 Algorithm

## 10 Comments

- 

## References